

Flexible Hole Location Gages

Titan hole location gages are used to check the centerline location of a threaded hole. They are flexible to provide a positive location on the pitch diameter of the part and can be used with a CMM or ordinary micrometers, in pairs.

INCH SIZES		PRICE	METRIC SIZES	PRICE
UNC	UNF			
	#0-80	127.00	M2x0.4	140.00
#1-64	#1-72	120.00	M4x0.7	133.00
#2-56	#2-64	117.00	M5x0.8	128.00
#3-48	#3-56	112.00	M6x1.0	113.00
#4-40	#4-48	105.00	M8x1.25	115.00
#6-32	#6-40	116.00	M10x1.25	116.00
#8-32	#8-36	111.00	M10x1.5	116.00
#10-24	#10-32	108.00	M12x1.25	120.00
#12-24	#12-28	105.00	M12x1.75	120.00
¼-20	¼-28	95.00	M12x1.5	120.00
5/16-18	5/16-24	95.00	M14x1.5	123.00
3/8-16	3/8-24	101.00	M14x2.0	123.00
7/16-14	7/16-20	101.00		
½-13	½-20	107.00		
5/8-11	5/8-18	107.00		
¾-10	¾-16	112.00		



- *Fast Track, Expedited Service Available*
- *Special Thread Plug & Ring Gages*
60°, ACME, JIS, DIN, Buttress and British Standards available on request.
- *Engineering assistance to solve any technical questions available from our staff.*
- *Quotes valid for 30 days*

WARRANTY

Titan Gage warrants all gages for 60 days from the date of shipment, except in cases of customer error or mishandling. This 60 days period allows ample time for all gages to be inspected for any manufacturing inaccuracies. Any- gage returned after the 60 days warranty period for defects will be subject to a rework charge.